



BOREAL BPI 00

Dimout media for digital printing.

Technical properties



Flame retardant



Acoustic

Applications Valences - Lining - Bed runners - Curtains - Roman blinds

Composition 100% FR polyester

Weight 260 g/m²

Width 145 cm

Fabric direction Standard Direction

Fitting ↔ cm ↓ cm

Maintenance advice      

Label OekoTex

Minimum order 25 linear(s) meter(s)

Technical characteristics

Flame retardant	M1 / IMO PASS	
Acoustic	Noise reduction coefficient (NRC) :	0.88
	Weighted sound absorption coefficient (a _w) :	0.90
	Acoustic absorption class (a _w) :	A
Optical index	Light reflexion :	63 %
	Light absorption :	36 %
	Light transmission :	1 %
Thermal index	Solar reflexion :	59 %
	Solar absorption :	40 %
	Solar transmission :	1 %
	UV transmission :	0 %
	Gtot :	Gt 38 % Fc 55 %
Resilience	Lightfastness (units Class/8)	6
	Dimensional Stability (%)	
	Warp	-1
	Weft	-2
	Martindale (Cycles)	0
	Breaking Elongation	
	Warp	28
	Weft	24
	Breaking load (daN)	
	Warp	120
Weft	78	

