



# BOREAL BPI 00

Dimout media for digital printing.

## Technical properties



Flame retardant



Acoustic

**Applications** Valences - Lining - Bed runners - Curtains - Roman blinds

**Composition** 100% FR polyester

**Weight** 260 g/m<sup>2</sup>

**Width** 280 cm

**Fabric direction** Room High Direction

**Fitting** ↔ cm ↓ cm

**Maintenance advice**      

**Label** OekoTex

**Minimum order** 25 linear(s) meter(s)

## Technical characteristics

Flame retardant	M1 / IMO PASS	
Acoustic	Noise reduction coefficient (NRC) :	<b>0.88</b>
	Weighted sound absorption coefficient (a <sub>w</sub> ) :	<b>0.90</b>
	Acoustic absorption class (a <sub>w</sub> ) :	<b>A</b>
Optical index	Light reflexion :	<b>63 %</b>
	Light absorption :	<b>36 %</b>
	Light transmission :	<b>1 %</b>
Thermal index	Solar reflexion :	<b>59 %</b>
	Solar absorption :	<b>40 %</b>
	Solar transmission :	<b>1 %</b>
	UV transmission :	<b>0 %</b>
	Gtot :	<b>Gt 38 % Fc 55 %</b>
Resilience	Lightfastness (units Class/8)	<b>6</b>
	Dimensional Stability (%)	
	Warp	<b>-1</b>
	Weft	<b>-2</b>
	Martindale (Cycles)	<b>0</b>
	Breaking Elongation	
	Warp	<b>28</b>
	Weft	<b>24</b>
	Breaking load (daN)	
	Warp	<b>120</b>
Weft	<b>78</b>	

